



CREATED BY: HOOSIER CRANE SERVICE

**CONFIDENTIAL**

**GORBEL**

600 FISHERS RUN  
P.O. BOX 593  
FISHERS, NY 14453-0593

MODEL NO.: FS300NP6-8-6

CAPACITY: 0.500 TON  
SPAN: 8'-0"  
H.U.B.: 8'-0"

QUANTITY: 1  
SHIPPING WT.: 819 LBS

DRAWN: lauyod

DATE: DEC 23, 2014

C.O.#: test

P/N: test.1A

- NOTES:
- 1) FOUNDATIONLESS REQUIREMENTS:
    - CENTERED ON A SQUARE FOOT AREA THAT IS FREE FROM CRACKS, SEAMS, AND WALLS.
    - REINFORCED CONCRETE WITH PRESSURE OF 3000 PSI AND SOIL PRESSURE OF 2500 PSF.
    - CHEMICAL ANCHOR BOLTS TO WITHSTAND A MINIMUM OF 3470 LBS. OF PULL OUT FORCE.
    - CONCRETE MUST CONTAIN WIRE MESH REINFORCEMENT.
  - 2) DO NOT SCALE FROM THIS DRAWING.
  - 3) OVERALL HEIGHT = 8'-6"