



6 BOLT  
 BASE BOLT PATTERN  
 1 1/4" BASE PLATE THICKNESS AT ANCHOR BOLT  
 VIEW A-A  
 NOT TO SCALE

REINFORCING RODS:  
 5/8"Ø ON TOP, 3/4"Ø ON BOTTOM,  
 LOCATED 12" ON CENTER

CREATED BY: HOOSIER CRANE SERVICE

**CONFIDENTIAL**

**GORBEL**

600 FISHERS RUN  
 P.O. BOX 593  
 FISHERS, NY 14453-0593

MODEL NO.: FS300-14-10

CAPACITY: 1.000 TON  
 SPAN: 12'-0"  
 H.U.B.: 12'-0"

QUANTITY: 1  
 SHIPPING WT.: 1624 LBS

DRAWN: lauyod      DATE: DEC 24, 2014

C.O.#: test      P/N: test.1A

- NOTES:
- 1) JIB CRANE FOUNDATION REQUIREMENTS ARE BASED ON A SOIL PRESSURE OF 2500 LBS PER SQUARE FOOT. CONCRETE RECOMMENDED FOR JIB CRANE FOUNDATION IS 3000 LBS PER SQUARE INCH OF COMPRESSIVE FORCE.
  - 2) DO NOT SCALE FROM THIS DRAWING.
  - 3) OVERALL HEIGHT = 12'-10"