



6 BOLT
BASE BOLT PATTERN
1/2" BASE PLATE THICKNESS AT ANCHOR BOLT
VIEW A-A
NOT TO SCALE

CREATED BY: HOOSIER CRANE SERVICE

CONFIDENTIAL

GORBEL

600 FISHERS RUN
P.O. BOX 593
FISHERS, NY 14453-0593

MODEL NO.: FS300NP6-8-6

CAPACITY: 0.250 TON
SPAN: 10'-0"
H.U.B.: 12'-0"

QUANTITY: 1
SHIPPING WT.: 949 LBS

DRAWN: lauyod

DATE: DEC 23, 2014

C.O.#: test

P/N: test.1A

- NOTES:
- FOUNDATIONLESS REQUIREMENTS:
 - CENTERED ON A SQUARE FOOT AREA THAT IS FREE FROM CRACKS, SEAMS, AND WALLS.
 - REINFORCED CONCRETE WITH PRESSURE OF 3000 PSI AND SOIL PRESSURE OF 2500 PSF.
 - CHEMICAL ANCHOR BOLTS TO WITHSTAND A MINIMUM OF 3470 LBS. OF PULL OUT FORCE.
 - CONCRETE MUST CONTAIN WIRE MESH REINFORCEMENT.
 - DO NOT SCALE FROM THIS DRAWING.
 - OVERALL HEIGHT = 12'-6"