



6 BOLT
 BASE BOLT PATTERN
 BASE PLATE THICKNESS AT ANCHOR BOLT
 VIEW A-A
 NOT TO SCALE

CREATED BY: HOOSIER CRANE SERVICE

CONFIDENTIAL

GORBEL

600 FISHERS RUN
 P.O. BOX 593
 FISHERS, NY 14453-0593

MODEL NO.: FS300NP6-8-6

CAPACITY: 0.500 TON
 SPAN: 8'-0"
 H.U.B.: 10'-0"

QUANTITY: 1
 SHIPPING WT.: 869 LBS

DRAWN: lauyod DATE: DEC 23, 2014

C.O.#: test P/N: test.1A

- NOTES:
- 1) FOUNDATIONLESS REQUIREMENTS:
 - CENTERED ON A SQUARE FOOT AREA THAT IS FREE FROM CRACKS, SEAMS, AND WALLS.
 - REINFORCED CONCRETE WITH PRESSURE OF 3000 PSI AND SOIL PRESSURE OF 2500 PSF.
 - CHEMICAL ANCHOR BOLTS TO WITHSTAND A MINIMUM OF 3470 LBS. OF PULL OUT FORCE.
 - CONCRETE MUST CONTAIN WIRE MESH REINFORCEMENT.
 - 2) DO NOT SCALE FROM THIS DRAWING.
 - 3) OVERALL HEIGHT = 10'-6"