



8'-0" SPAN
71" TROLLEY TRAVEL
17 3/8"
17"
22 1/2"
8"
2 1/2"
12"
36" DIA BOLT CIRCLE
1 1/4" DIA BOLT
2" OFFSET TYP
4"
8'-0" H.U.B.
1 1/4" BASE PLATE THICKNESS AT ANCHOR BOLT
12 BOLT PATTERN
VIEW A-A
NOT TO SCALE
REINFORCING RODS:
5/8" φ ON TOP, 3/4" φ ON BOTTOM
LOCATED 12" ON CENTER

CONFIDENTIAL

GORBEL
600 FISHERS RUN
P.O. BOX 593
FISHERS, NY 14453-0593

MODEL NO.: FS300-16-12
CAPACITY: 3.000 TON
SPAN: 8'-0"
H.U.B.: 8'-0"
QUANTITY: 1
SHIPPING WT.: 1974 LBS

DRAWN: lauyod
C.O.#: test

DATE: DEC 26, 2014
P/N: test.1A

- NOTES:
- 1) JIB CRANE FOUNDATION REQUIREMENTS ARE BASED ON A SOIL PRESSURE OF 2500 LBS PER SQUARE FOOT. CONCRETE RECOMMENDED FOR JIB CRANE FOUNDATION IS 3000 LBS PER SQUARE INCH OF COMPRESSIVE FORCE.
 - 2) DO NOT SCALE FROM THIS DRAWING.
 - 3) OVERALL HEIGHT = 9'-0"

8'-0" SQUARE